

Name	Value	Unit
Safety information 1	In grounded power lines	
Packaging type	BOX	
Ratings per	EN 60664	
Rated voltage (II / 2) [V]	450	V
Rated impulse voltage (II / 2) [kV]	4	kV
Rated current [A]	32	A
Legend (ratings)	(II / 2) \triangleq Overvoltage category II / Pollution degree 2	
Type of wiring	Side-entry wiring	
Total number of connection points	3	
Total number of potentials	1	
Connection technology	CAGE CLAMP®	
Actuation type	Operating lever	
Connectable conductor materials	Copper	
Nominal cross section	4 mm ²	
Solid conductor	0.2 ... 4 mm ² / 24 ... 12 AWG	
Stranded conductor	0.2 ... 4 mm ² / 24 ... 12 AWG	
Fine-stranded conductor	0.14 ... 4 mm ² / 24 ... 12 AWG	
Strip length	11 mm / 0.43 Inch	
Width	18.7 mm / 0.736 Inch	
Height	8.3 mm / 0.327 Inch	
Depth	18.6 mm / 0.732 Inch	
Color	transparent	
Flammability class per UL94	V2	
Weight [g]	2.527	g
Ambient temperature (operation)	85 °C	
Continuous operating temperature up to [°C]	105	°C

T-Marking per EN 60998	T85	
Main product function	Hebelklemme	
Product type	Splicing connectors	