Specificații

Eaton 248849

Eaton Z-SCH Installation contactor, 230VAC/50Hz, 2N/O+2N/C, 25A, 2HP

General specifications	
PRODUCT NAME	Eaton Z-SCH contactor
CATALOG NUMBER	248849
EAN	4015082488499
PRODUCT LENGTH/DEPTH	85 mm
PRODUCT HEIGHT	60 mm
PRODUCT WIDTH	35 mm
PRODUCT WEIGHT	0.22 kg
COMPLIANCES	RoHS conform
MODEL CODE	Z-SCH230/25-22

Powering Business Worldwide

Specificaţii produs

AMPERAGE RATING	25 A
FEATURES	Additional equipment possible
DEGREE OF PROTECTION	IP40
EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT	6 W
AMBIENT OPERATING TEMPERATURE - MAX	60 °C
AMBIENT OPERATING TEMPERATURE - MIN	-40 °C
HEAT DISSIPATION CAPACITY	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT	0 W
INCANDESCENT LAMP LOAD - MAX	3000 W
LOAD FLUORESCENT LAMP - MAX	1160 VA
LOAD FLUORESCENT LAMP (DUO CIRCUIT) - MAX	2552 VA
LOAD FLUORESCENT LAMP (PARALLEL COMPENSATED) - MAX	1044 VA
NUMBER OF CONTACTS (NORMALLY CLOSED CONTACTS)	2
NUMBER OF CONTACTS (NORMALLY OPEN CONTACTS)	2
NUMBER OF MODULAR SPACINGS	2
RATED OPERATING VOLTAGE (UE) - MAX	440 V
RATED OPERATING VOLTAGE (UE) - MIN	440 V
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	25 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT	0 W
UTILITY CATEGORY	1
VOLTAGE RATING (EXCITATION) - MAX	253 V
VOLTAGE RATING (EXCITATION) - MIN	195.5 V

Resurse

DESENE	eaton-3d-drawing-sch-pack.jpg eaton-3d-drawing-z-r-sch-einbau.jpg eaton-wiring-diagram-z-sch-klem-bez4.jpg eaton-dimensions-ma-sch40.jpg

BUILT-IN DEPTH	60 mm
VOLTAGE TYPE	AC
UTILIZATION CATEGORY (ACCORDING TO EN IEC 60947-4-1)	AC-1

DENUMIREA PROIECTULUI:
NUMĂRUL PROIECTULUI:
PREGĂTIT DE:
DATA:

Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlanda
Eaton.com

© 2026 Eaton. Toate drepturile rezervate

Urmăriți-ne pe rețelele de socializare pentru a obține cele mai noi informații despre produse și asistență.