

Specificații



Eaton 103104

Eaton xComfort BF LV systems Final Distribution Boards. Complete surface-mounted flat distribution board with window, white, 24 SU per row, 4 rows, type C

General specifications

PRODUCT NAME	Eaton xComfort BF small distribution board
CATALOG NUMBER	103104
EAN	4015081029433
PRODUCT LENGTH/DEPTH	770 mm
PRODUCT HEIGHT	150 mm
PRODUCT WIDTH	560 mm
PRODUCT WEIGHT	11.8 kg
COMPLIANCES	RoHS conform
CERTIFICATIONS	IEC/EN 62208 IEC/EN 61439-3 IEC/EN 61439-1
MODEL CODE	BF-OT-4/96-C



Powering Business Worldwide

Specificații produs

USED WITH	BF flat distribution board Installation distribution board Basic device
SPECIAL FEATURES	<ul style="list-style-type: none"> • IP30 • Protection Class I • Steel sheet enclosure white (RAL 9016)
TYPE	<ul style="list-style-type: none"> • Basic device • BF flat DBO • Installation distribution boards
FEATURES	EMC-version Earthing terminal block Neutral terminal block Signal passing door
10.10 TEMPERATURE RISE	The panel builder is responsible for the temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility.
10.13 MECHANICAL FUNCTION	Meets the product standard's requirements.
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Not relevant to indoor installations.
10.2.5 LIFTING	Does not apply to enclosures without lifting aids.

Resurse

BROȘURI	eaton-xcomfort-compact-distribution-boxes-brochure-br014015en-en-us.pdf
DESENE	eaton-xcomfort-bf-lv-systems-dimensions.eps

10.2.6 MECHANICAL IMPACT	IK07
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	IP30
10.4 CLEARANCES AND CREEPAGE DISTANCES	Is the panel builder's responsibility.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	< 0.1 Ω; meets the product standard's requirements.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Is the panel builder's responsibility.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Ui = 415 V AC
10.9.3 IMPULSE WITHSTAND VOLTAGE	Does not apply to basic enclosures as defined in EN 62208.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Does not apply to metal enclosures.
FITTED WITH:	DIN rail mounting frame Door with three-point turn-lock Front plates Enclosure Cable gland plate inserts (top) Neutral-/protective conductor terminal
ENCLOSURE MATERIAL	Steel
BUILT-IN HEIGHT	150 mm
BUILT-IN WIDTH	560 mm
CABLE ENTRY POSTION	Cable entries on top and bottom
TERMINAL TYPE	Screw terminals
BUILT-IN DEPTH	770 mm
HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	51 W
HEAT DISS. AMBIENT 35°C DELTA T: 20°C WALL MOUNT MIDDLE ENCL.	47 W

TOP (IEC 60890)	
HEAT DISS. AMBIENT 35°C DELTA T:20°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	49 W
CLOSURE TYPE	Other
COVER/DOOR COLOR	Transparent
COVER/DOOR MODEL	With notch
COVER/DOOR TYPE	Door Single
RAL-NUMBER	9016
WIDTH IN NUMBER OF MODULAR SPACINGS	24
AMBIENT OPERATING TEMPERATURE DETAILS	-5 °C - 40 °C
APPLICATION	Indoor (installation site)
VOLTAGE RATING AT AC	415 V AC
COLOR	White Traffic white (RAL 9016)
NUMBER OF ROWS	4
FREQUENCY RATING OF CONTACTS	50 Hz / 60 Hz
MODULE RACK TYPE	Rail frame
DEGREE OF PROTECTION	IK07 (impact resistance) IP30
NUMBER OF MODULE SPACE UNITS PER ROW	24
PROTECTION CLASS	I (earthed)
PROTECTIVE SHROUDING MATERIAL	Metal
FUNCTIONS	Basic device Sealable
MATERIAL	Sheet steel, powder- coated
MOUNTING METHOD	Surface mounted (plaster) Surface mounting DIN-rail
HEAT DISS. AMBIENT 35°C DELTA T:35°C WALL MOUNT INDIVID. ENCL. TOP (IEC 60890)	103 W
HEAT DISS. AMBIENT 35°C DELTA T: 35°C WALL MOUNT MIDDLE ENCL. TOP (IEC 60890)	94 W
HEAT DISS. AMBIENT 35°C DELTA T:35°C WALL MOUNT STARTING ENCL. TOP (IEC 60890)	98 W

INTERNAL DEPTH	131 mm
PE AND N TERMINAL NUMBER AND CROSS SECTION	N: 2 x 25 mm ² + 43 x 16 mm ² PE: 2 x 25 mm ² + 43 x 16 mm ²
NUMBER OF OPENINGS FOR SOCKET OUTLETS	0

DENUMIREA PROIECTULUI:

NUMĂRUL PROIECTULUI:

PREGĂTIT DE:

DATA:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlanda
Eaton.com

© 2026 Eaton. Toate drepturile rezervate

Urmăriți-ne pe rețelele de socializare pentru a obține cele mai noi informații despre produse și asistență.

