



Eaton 281196

Eaton Moeller® series DILM Interlock, mechanical, for DILM7-15

General specifications

PRODUCT NAME	Eaton Moeller® series DILM interlock
CATALOG NUMBER	281196
EAN	4015082811969
PRODUCT LENGTH/DEPTH	70 mm
PRODUCT HEIGHT	4 mm
PRODUCT WIDTH	22 mm
PRODUCT WEIGHT	0.003 kg
CERTIFICATIONS	UL Category Control No.: NLDX UL 508 CSA-C22.2 No. 14-05 UL File No.: E29096 CSA CE CSA File No.: 012528 IEC/EN 60947-4-1 UL CSA Class No.: 3211-04
MODEL CODE	DILM12-XMV

General information

ACCESSORY/SPARE PART TYPE	Mechanical locking
----------------------------------	--------------------

PRODUCT CATEGORY	Accessories
-------------------------	-------------

Climatic environmental conditions

AMBIENT OPERATING TEMPERATURE - MIN	-25 °C
--	--------

AMBIENT OPERATING TEMPERATURE - MAX	60 °C
--	-------

Design verification

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT PVID	0 W
HEAT DISSIPATION CAPACITY PDISS	0 W
HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT PVID	0 W
RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN)	0 A
STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT PVS	0 W
10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.

Resurse

DESENE	eaton-contactors-interlock-dilm-3d-drawing-002.eps
INSTRUCȚIUNI DE INSTALARE	eaton-mechanical-interlock-dilm-xmv-il03407029z.pdf eaton-contactor-accessories-dilm-x-il03406009z.pdf
MCAD MODEL	dil_m12_xmv.stp

10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	Not applicable.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

DENUMIREA PROIECTULUI:

NUMĂRUL PROIECTULUI:

PREGĂTIT DE:

DATA:



Eaton Corporation plc Eaton House
 30 Pembroke Road
 Dublin 4, Irlanda
 Eaton.com

Urmăriți-ne pe rețelele de socializare pentru a obține cele mai noi informații despre produse și asistență.

© 2026 Eaton. Toate drepturile rezervate

